

DESCRIPTION

PENECLEANER™ A PLUS is specially formulated solvent and cleaner for epoxy and polyurethane materials, e.g. PENEPOX™ και PENEPOX™, polyurethane sealants, etc. It is used as a thinner for the PENEPOX™ polyurethane coatings.

RECOMMENDED FOR

PENECLEANER™ A PLUS can be used as a thinner for the liquid membrane systems:

- ▶ PENEPOX™ ELASTIC, PENEPOX™ CLEAR

PENECLEANER™ A PLUS can be used as a cleaning solvent for the following systems:

- ▶ PENEPOX™ CLEAR MAT FINISH, PENEPOX™ TOP CLEAR
- ▶ PENEPOX™-CS, PENEPOX™-W, PENEPOX™-SF ELASTIC, PENEPOX™-SF PRIMER
- ▶ PENEPOX™ POOL, PENEPOX™ SL

ADVANTAGES

- ▶ Excellent compatibility with one component liquid-applied polyurethane coatings
- ▶ Excellent solubility
- ▶ Easy to apply – airless spray or nap roller

TECHNICAL CHARACTERISTICS

<i>Type</i>	Polyurethane solvent
<i>Form</i>	Liquid
<i>Color</i>	Clear
<i>Density</i>	Approx.0,9 kg/L (62 lb/ft ³)

DIRECTIONS FOR USE

Application: Mix thoroughly the content of PENECLEANER™ A PLUS container, using a mechanical mixer (mixing drill with a mixing wand), before use.

Application Rates:

PENEPOX™ ELASTIC: Pour and mix thoroughly 4 to 8% (by weight) PENECLEANER™ A PLUS with PENEPOX™ ELASTIC, using a mechanical mixer (mixing drill with a mixing wand).

PENEPOX™ CLEAR: Pour and mix thoroughly the desired quantity of PENECLEANER™ A PLUS with PENEPOX™ ELASTIC, using a mechanical mixer (mixing drill with a mixing wand). Contact PENETRON HELLAS S.A. for further details regarding your project.

SPECIAL CONSIDERATIONS

Contact PENETRON ROMANIA for further information, regarding your project, the use, the mixing ratios and the products that are compatible with PENECLEANER™ A PLUS.

PACKAGING

PENECLEANER™ A PLUS is available in 1 kg, 4 kg and 16 kg containers.

STORAGE / SHELF LIFE

PENECLEANER™ A PLUS can be stored for 18 months in its original packing (unopened container) at 5 °C – 30 °C (41 °F – 86 °F) in a cool, dry place. Keep away from wet areas and direct sunlight.

SAFE HANDLING INFORMATION

PENECLEANER™ A PLUS contains methylethylketone. Flammable. Avoid skin and eye contact. If contact is made, flush areas with lots of water and seek medical advice. Protective gloves, mask and goggles should be worn. For further information please refer to Safety Data Sheet. Each Safety Data Sheet contains health and safety information for the protection of your employees and your customers. KEEP OUT OF REACH OF CHILDREN.

WARRANTY - DISCLAIMER

BEST IMPORT PRODUCTS PENETRON warrants that the products manufactured by it shall be free from material defects and will conform to formulation standards and contain all components in their proper proportion. Should any of the products be proven defective, the liability to BEST IMPORT PRODUCTS PENETRON shall be limited to replacement of the material proven to be defective, and BEST IMPORT PRODUCTS PENETRON shall in no case be liable otherwise or for incidental or consequential damage. BEST IMPORT PRODUCTS PENETRON MAKES NO WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED. User shall determine the suitability of the product for its intended use and assume all risks and liability in connection therewith. BEST IMPORT PRODUCTS PENETRON may particularly differentiate its versions of the product's data sheet compared with those of PENETRON INTERNATIONAL LTD or respective PENETRON companies worldwide. These changes are due to text formatting, different application weathering and procedures or different product names and aim at the optimal consumer information.