

THIXOTROPIC AGENT IN WHITE POWDER FORM

DESCRIPTION

STELLMITTEL 3 SUPER is a thixotropic agent, in white powder form. Thickening agent for multiple thixotropic coatings, vertical surfaces, covings, etc. Not suitable for PU 410.

RECOMMENDED FOR

- ▶ Thixotropic agent for coatings e.g. EP 200 VF for coatings with slope.
- ▶ Thixotropic agent for resin mortar e.g. EP 150 for concave and triangular covings.

ADVANTAGES

- ▶ Easy to apply. Ready to use.

TECHNICAL CHARACTERISTICS

<i>Type</i>	White Powder
<i>Density</i>	50 g/l
<i>Dosage</i>	2-5 by weight of resin, depending on the application

The aforementioned results are related to average laboratory test results. In reality the climate changes, such as temperature, moisture and surface porosity may change these results.

DIRECTIONS FOR USE

Surface preparation: Mix the resin with the hardener according to the instructions in the technical data sheet. Afterwards, add the thixotropic agent STELLMITTEL 3 SUPER to the required dosage and continue the mixing. If necessary add more product. e.g. for resin mortar add 120-150 g (about 3 liters of volume).

NOTE: The surface preparation is very important for optimum result and high durability.

SPECIAL CONSIDERATIONS

Contact PENETRON ROMANIA for further information, regarding your project.

PACKAGING

STELLMITTEL 3 SUPER is available 1.5 kg container.

STORAGE / SHELF LIFE

When stored in dry rooms, protected against UV and heat the shelf life is unlimited.

SAFE HANDLING INFORMATION

Avoid skin and eye contact. If contact is made, flush areas with lots of water and seek medical advice. Protective gloves, mask and goggles should be worn. For further information please refer to Safety Data Sheet
KEEP OUT OF REACH OF CHILDREN.

THIXOTROPIC AGENT IN WHITE POWDER FORM

WARRANTY – DISCLAIMER

BEST IMPORT PRODUCTS PENETRON. warrants that the products manufactured by it shall be free from material defects and will conform to formulation standards and contain all components in their proper proportion. Should any of the products be proven defective, the liability to BEST IMPORT PRODUCTS PENETRON. shall be limited to replacement of the material proven to be defective, and BEST IMPORT PRODUCTS PENETRON shall in no case be liable otherwise or for incidental or consequential damage.

BEST IMPORT PRODUCTS PENETRON MAKES NO WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED. User shall determine the suitability of the product for its intended use and assume all risks and liability in connection therewith.

BEST IMPORT PRODUCTS PENETRON may particularly differentiate its versions of the product's data sheet compared with those of PENETRON INTERNATIONAL LTD or respective PENETRON companies worldwide. These changes are due to text formatting, different application weathering and procedures or different product names and aim at the optimal consumer information